



## **KAMSONS CHEMICALS PVT. LTD.**

Plot No. A-726, T.T.C. Industrial Area, Village Mahape,  
Thane Belapur Road, Dist. Thane, Navi Mumbai.

Ph : 022-27780767, 022-27780768. Fax : 022-26854438

---

### **TECHNICAL DATA SHEET**

#### **KAMICRYL - 295**

CHEMICAL COMPOSITION :	STYRENE - ACRYLIC CO-POLYMER EMULSION
APPEARANCE :	MILKY WHITE EMULSION
SOLID CONTENT (105 °C - 1½ HRS) :	50% ± 1%
pH (AS PACKED) :	8 - 10
Viscosity at 30 °C in Brookfield : Viscometer spindle 4 / 20 rpm :	1500 - 4500 cps
PARTICLE SIZE :	LESS THAN 0.1 MICRON
FREE MONOMER :	LESS THAN 0.5
CHARGE :	ANIONIC
PROPERTIES :	EXTREMELY HIGH PIGMENT LOADING CHARACTERISTIC & ALKALI RESISTANCE

**Application** : **Kamicryl-295** is used for the production of high-gloss to matt indoor and outdoor coatings for application on plaster, masonry, asbestos, cement, concrete, wood, and other substrates. Moreover, **Kamicryl-295** is used as an impregnating agent, primer, binder for textured finishes, base material for producing adhesives for a great variety of applications, and as an additive for hydraulic binders.

**Storage** : When kept in tightly closed containers in a cool but frost free place, **Kamicryl-295** can be stored for 12 months.

---

THESE SUGGESTIONS & DATA ARE BASED ON INFORMATION, WE BELIEVE TO BE RELIABLE. THEY ARE OFFERED IN GOOD FAITH, BUT WITHOUT GUARANTEE, AS CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL.

---