



TEXTURE COATINGS & ROOF POINTING COMPOUNDS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMICRYL 295	GENERAL PURPOSE STYRENE ACRYLIC EMULSION	TEXTURE & PAINT COATING	18° C	50%±2
KAMICRYL 61	100% ACRYLIC EMULSION	EXCELLENT DURABILITY, ADHESION, GLOSS AND WATER RESISTANCE, DESIGNED FOR TEXTURE COATINGS, MARBLE FINISHES,MASONRY COATINGS AND AS A CO-BINDER IN ELASTOMERIC WALL COATINGS	17 °C	50 ±1 %
KAMICRYL 3045	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE CONCRETE ADMIXTURE AND INTERIOR AND EXTERIOR PAINTS, TEXTURED COATINGS	20 °C	45 ± 1 %
KAMICRYL 3040	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE CONCRETE ADMIXTURE AND INTERIOR AND EXTERIOR PAINTS, TEXTURED COATINGS	18°C	40± 1 %
KAMICRYL 51 AP	AQUEOUS ACRYLIC /STYRENE COPOLYMER DISPERSION	SUPERIOR ADHESION AND WATER RESISTANCE, EXCELLENT GLOSS FOR CLEAR GLAZE COATINGS	20 °C	50 ± 1 %

ELASTOMERIC & WATERPROOFING COATINGS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAM 2SC HYB	PURE ACRYLIC HYBRID EMULSION	EXTERIOR MEMBRANES, COMPLIES AUSTRALIAN CSIRO AS4858 CLASS III WET AREA WATERPROOFING STANDARD	1° C	50%±2
KAMTHANE RAR THX	ACRYLIC POLYURETHANE HYBRID EMULSION	ARCHITECTURAL EXTERIOR HIGH BUILD ELASTOMERIC COATINGS	- 22° C	47%±2
KAMICRYL 2505	100% ACRYLIC COPOLYMER	PREMIUM ELASTOMERIC HIGH BUILD, TEXTURE AND ROOF COATINGS	-22°C	50 ± 1 %
KAMTHANE 1408	100% WATER BASED UV STABLE ACRYLIC POLYURETHANE HYBRID DISPERSION	BINDER FOR ELASTOMERIC ROOF COATINGS	-12 °C	48 ± 1 %
KAMICRYL 300	STYRENE ACRYLIC HYBRID DISPERSION	PROVIDES COATINGS WITH A GOOD BALANCE OF ELONGATION, TENSILE STRENGTH AND ALSO FOR ELASTOMERIC MASONRY APPLICATIONS	- 8 °C	50 ±1 %
KAMICRYL 7643	AQUEOUS ANIONIC DISPERSION	FOR MANUFACTURING OF FLOORING ADHESIVES AND PRESSURE SENSITIVE DISPERSION, FLEXIBLE COATINGS, BOPP TAPES APPLICATIONS	- 43 °C	62 ± 1%
KAMICRYL 117	ACRYLIC EMULSION	USED FOR BOPP TAPES,JUMBO ROLLS, HOLOGRAMS AND SUIT CASE INNER LINING etc.	- 41 °C	53-55%

MISCELLANEOUS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMSPERSE OR 25	SODIUM POLYACRYLATE	DISPERSING AGENT SOLUTION	N/A	25%±2
KAMICRYL 5360	ACRYLIC THICKNER	VISCOSITY MODIFIER	N/A	25%±2
KAMHYB PU 88	PU THICKNER	VISCOSITY MODIFIER	N/A	25%±2
KAMICRYL 5320	SODIUM POLYACRYLATE GEL	IDEAL FOR THICKENING ALL TYPES OF WATER BASED PAINTS AND LATEX COMPOUNDS	63°C	20 ± 1 %
KAMWAX 1429	PARAFFIN/POLYETHYLENE WAX EMULSION	OVERPRINT VARNISH, INDUSTRIAL COATING AND FUNCTIONAL PACKAGING COATING APPLICATIONS	N/A	40 ± 1
KAMWAX PE 40	NON-IONIC EMULSION OF AN OXIDIZED HD POLYETHYLENE WAX	IMPROVES THE SCRATCH RESISTANCE IN AQUEOUS COATINGS ,PRINTING INKS AND ALSO USED IN SELF SHINE FLOOR CARE PRODUCTS	N/A	35% ± 1
KAMICRYL ELASTOFALT	ALIPHATIC POLYURETHANE MODIFIED BITUMEN EMULSION	WATERPROOFING/CURING MEMBRANE AND PROTECTIVE COATINGFOR SUB STRUCTURE	-6°c	60 ± 1
KAMICRYL 5010	SOLVENT BASED ACRYLIC RESIN USED IN THE FORMULATION OF LACQUERS AND SPECIALTYCOATINGS	METALS, PLASTICS,WOOD AND CONCRETE	N/A	N/A
KAMICRYL 501	SOLVENT-BASED ACRYLIC ADHESIVE WHERE PERMAN- ENT TACK AND HIGH PEEL STRENGTHS ARE REQUIRED	MANUFACTURE OF TAPES LIKE BOPP/ PVC/ PET/ CELLOPHANE/ PAPER	N/A	N/A
SEALCOAT	WATERPROOFING ELASTOMERIC EXTERIOR MEMBRANE COATING	DUAL PROPERTIES OF WATERPROOFING & AESTHETIC EXTERIOR PAINT	N/A	N/A
KAMFLEX WP	SINGLE PACK AQUEOUS PUD- BASED WATERPROOFING ME- MBRANE / PREMIUM EXTERI- OR ELASTOMERIC PAINT	ROOFS	N/A	N/A
KAMICRYL DURATEX	WATER-BASED PU PAINT	SPEAKER CABINET TEXTURE COATING (MDF OR PLYWOOD)	N/A	N/A

+91-22-4202 9999
+91-98197-54448
response@kamsons.com/info@kamsons.net
www.kamsons.com

Suite No. 1003, 10th Floor, Embassy Chambers, 3rd Road, Khar(W), Mumbai-400052. Maharashtra, India



KAMSONS POLYMERS PVT. LTD.

ISO 9001 : 2015 CERTIFIED COMPANY

WATER BASED ACRYLIC EMULSIONS

Maximising the power of polymers...

CONCRETE MODIFICATIONS & ADMIXTURES

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMICRYL 76	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE CONCRETE ADMIXTURE	18°C	48%±2
KAMICRYL 400	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE FLEXIBLE CONCRETE MODIFICATION	− 8°C	57%±2
KAMICRYL 295	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE CONCRETE ADMIXTURE	20°C	50%±2
KAMICRYL 3036	STYRENE ACRYLIC EMULSION	GENERAL PURPOSE CONCRETE ADMIXTURE AND MORTOR APPLICATIONS	15 °C	36 ± 1 %

SELF PRIMING DIRECT TO CONCRETE COATINGS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMICRYL 31 SC HG	ACRYLIC EMULSION	NANO CONCRETE PRIMER	35°C	47%±2
KAMICRYL 60 SC HG	SELF-CROSSLINKING ACRYLIC COPOLYMER EMULSION	MANUFACTURING OF WATER-BASED GLOSS ENAMELS, APPLICABLE ON WIDE VARIETY OF SUBSTRATES eg.METALS, CONCRETE, MASONRY, GLASS, WOOD etc.	60 °C	46 ± 1 %
KAMCRYL CS 0002	WATER-BASED HYBRID POLYURETHANE EMULSION	CONCRETE SEALER PRIMER	35°C	20 ±1 %
KAMCRYL CS 0003	ULTRA PREMIUM WATER-BASED CONCRETE SEALER	USED FOR TOPCOAT APPLICATION OVER EPOXY COATINGS ON CONCRETE SUBSTRATES, HIGHLY DURABLE AND SUITABLE FOR MEDIUM TRAFFICABLE DRIVEWAYS, PATHWAYS, CAR PARKS AND GARAGE FLOORS	20°C	30 ± 1 %

FAST CURE

PRODUCT	TYPE	RECOMMENDED APPLICATIONS	SOLIDS	VISCOSITY	T ₉
Kamicroyl 298 FCX	Crosslinked styrene acrylic emulsion	Texture and roofing pointing, fast cure	50±2%	2000 to 10000cps	19°C
Kamicroyl 7660 M	100% Acrylic Emulsion	Used for fast drying flexible coating, waterbased sealants and road marking paints	60±2%	50 to 500 cps	-25°C
Kamicroyl 24 FCX	100% Acrylic Emulsion	Used for fast drying paints and coating, road marking paints	49%	16 to 60 cps	17°C

SELF-CROSSLINKING COATINGS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMICRYL 2 ST ZX	SELF-CROSSLINKING STYRENE ACRYLIC EMULSION	EXTERIOR FLEXIBLE COATING FOR WOOD & FACADES	11°C	55%±2
KAMICRYL 12 SC ZX	SELF-CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR FOR TIMBER & WALL COATINGS	14°C	50%±2
KAMICRYL 24 SC ZX	SELF-CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR COATINGS FOR ROOFS & FACADES	24°C	50%±2
KAMICRYL 35 SC ZX	SELF-CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR COATINGS FOR ROOFS & VARIOUS SUBSTRATES	37°C	50%±2
KAMICRYL 48 SC ZX	SELF-CROSSLINKING PURE ACRYLIC EMULSION	EXTERIOR COATINGS FOR ROOFS & FACADES	44°C	50%±2
KAMICRYL 63 SCX	ACRYLIC CROSSLINKING EMULSION	HIGH GLOSS ENAMELS	43°C	48%±2

ADVANCED SPECIALITY ARCHITECTURAL COATINGS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMICRYL PR C35	ALL ACRYLIC EMULSION	SUPERIOR STAIN RESISTANCE/ METAL ADHESION. EXTERIOR & INTERIOR COATINGS	36°C	52%±2
KAMICRYL K10 AP	AQUEOUS ACRYLIC/STYRENE COPOLYMER DISPERSION	USED FOR HIGH GLOSS TO MATT INDOOR AND OUTDOOR COATINGS FOR APPLICATION ON PLASTER, MASONRY, ASBESTOS CEMENT, CONCRETE, WOOD AND OTHER SUBSTRATES AND ALSO AS A IMPREGNATING AGENT, PRIMER, BINDER FOR TEXTURED FINISHES	20 °C	50 ±1 %
KAMICRYL K 30	100% APEO/FORMALDEHYDE/AMMONIA FREE ACRYLIC EMULSION	USED FOR THE FORMULATION OF PREMIUM QUALITY EXTERIOR MASONRY PAINTS AND TEXTURED FINISHES, EXCELLENT GLOSS FOR CLEAR GLAZE COATINGS	35°C	47 ±1 %

TIMBER COATINGS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMICRYL 24 SC WX	PURE ACRYLIC EMULSION	WOOD COATING	24°C	30%
KAMICRYL 31 SC HG WX	NANO PARTICLE SIZE PURE ACRYLIC EMULSION	WOOD COATING	35°C	30%
KAMICRYL 35 SC WX	PURE ACRYLIC EMULSION	WOOD COATING	37°C	30%

GRAPHIC ARTS, OVERPRINT VARNISH & INKS

PRODUCT DESCRIPTION	TYPE	RECOMMENDED APPLICATIONS	TG	SOLIDS
KAMICRYL 2090	HARD STYRENE ACRYLIC NON FILM FORMING EMULSION	HIGH OPTICAL CLARITY & GLOSS. FAST DRY. GOOD HEAT RESISTANCE	110°C	44%±2
KAMICRYL 2074 OR	FLEXIBLE STYRENE ACRYLIC FILM FORMING EMULSION	FLEXO AND GRAVURE INKS ON FLEXIBLE PLASTIC FILM & FOIL.	− 9°C	48%±2
KAMICRYL 361	STYRENE ACRYLIC WITH GOOD HIDING POWER & OPACITY PROPERTIES. FAST DRYING	FOR PAPER & LOW COST CORRUGATED INKS. IMPROVES TRANSFER & HIDING POWER.	75°C	50%±2
KAMICRYL OPV HG 8000	READY WATER BASED OPV	ULTRA HIGH GLOSS	N/A	N/A
KAMICRYL OPV GL 60	READY WATER BASED OPV	GENERAL PURPOSE GLOSS	N/A	N/A
KAMICRYL OPV MATTE 15	READY WATERBASED OPV	MATT VARNISH	N/A	N/A
KAMICRYL OPV SATIN 30	READY WATERBASED OPV	SATIN VARNISH	N/A	N/A
KAMICRYL 6390	ALKALI SOLUBLE ACIDIC EMULSION	GOOD GRINDING PROPERTIES & COLOUR ACCEPTANCE. GOOD LET DOWN VEHICLE	N/A	42%±2
KAMICRYL 2089	STYRENE ACRYLIC COPOLYMER EMULSION	USED FOR OVERPRINTS VARNISHS. FLEXOGRAPHIC AND GRAVURE INKS ON PAPER AND PAPERBOARD TO ENHANCE GLOSS, CLARITY	98°C	48–50 %
KAMICRYL 2074	ACRYLIC POLYMER EMULSION	USED FOR OVERPRINT VARNISHES THAT REQUIRE GLOSS, HOLDOUT, WATER AND GREASE RESISTANCE	-16	45- 47%
KAMICRYL OPV 2140	HI-TECH WATERBASED ACRYLIC	READY TO USE OVERPRINT VARNISHES	N/A	40 ± 1 %
KAMICRYL OPV 2138	HI-TECH WATERBASED ACRYLIC	READY TO USE OVERPRINT VARNISHES	N/A	38 to 40 %
KAMICRYL OPV 2132	FAST DRYING EMULSION	EMULSION WITH A SMOOTH GLOSSY FINISH, PROVIDING OPTIMUM TRANSPARENCY FOR LEVEL OF GLOSS, SUITED FOR DOUBLE-SIDED COATING APPLICATION	N/A	33 ± 1 %
KAMICRYL 2038	STYRENE ACRYLIC COPOLYMER EMULSION	EXCELLENT PIGMENT WETTING AND GOOD RESOLUBILITY FOR PIGMENT DISPERSION, FLUID INKS AND OVERPRINT VARNISHES	87°C	34 ± 1 %
KAMICRYL 362	HIGH MOLECULAR WEIGHT ACRYLIC RESIN	MANUFACTURE OF HIGH SOLIDS, LOW VISCOSITY PIGMENT DISPERSIONS THAT HAVE EXCELLENT RHEOLOGY, FLOW AND STABILITY	28-30 °C	33 ± 1 %
KAMICRYL 4110	WATERBASED ACRYLIC COLLOIDAL ACIDIC EMULSION	FOR FLEXOGRAPHIC INKS, GOOD LET DOWN VEHICLE, GOOD GRINDING PROPERTIES	30°C	44 ± 1%
KAMICRYL KI 36	AQUEOUS ACRYLIC COPOLYMER EMULSION	BINDER FOR AQUEOUS FLEXOGRAPHIC INKS, CLEAR AND PIGMENTED COATINGS INCLUDING AQUEOUS DIP COATINGS FOR BRASS, COPPER, STEEL AND OTHER FINISHED GOODS	32°C	34 ± 1 %



KAMSONS POLYMERS PVT. LTD.

